

# FLUID RECLAIM EQUIPMENT



	Page
Oil King™	264
Coolant King™	265
Oil Ace™	266-268
16-Gallon Mobile Receiver	269
Big Hauler™ Truck Drain	270
Track Receivers	270
Diaphragm Evacuation Pumps	271
Evacuation Pump Packages	272-274
Fluid Reclaim Accessories	275-277

## Pressurized Oil Drain

Drain, evacuate and transfer used oil reliably, quickly and in the most cost-effective manner.

**5 Year  
Warranty!**

### Large Offset Collection Pan

23 inch (58 cm) diameter offset collection bowl gives you a 31 inch (79 cm) total reach.

### Superior Maneuverability

Wider and thicker handle for comfort.

### Easy to Drain

Pressurize using shop air for easy oil evacuation.

### Large 24-Gallon (90 l) Capacity Receiver

Perfect for small to large shops without an evacuation system.

### Liquid Sight Gauge

Easy-to-read tank-level gauge lets you know when the tank is full.

### Large Casters

Easily move around rough shop floors.



#### Typical Applications

- Automotive dealerships
- Fast lube centers
- Service shops
- Heavy-duty dealerships
- Fleet services facilities

#### Typical Fluids Handled

- Used oil

#### Technical Specifications

Fluid	Used oil
Fluid Capacity	24 gal (91 l)
Evacuation	Pressurized
Receiver Material	Steel
Length	24 in (60 cm)
Width	16 in (40.6 cm)
Height	56 to 80 in (143.5 to 203 cm)
Funnel Size	24 in (61 cm) diameter
Dry Weight	74 lb
Instruction Manual	310864

#### Ordering Information

Part Number	Description
119577	24 gal (90 l) steel-tank pressurized oil drain

## Vacuum-Assisted Oil Collection System

Large-capacity collection systems make removing drain plugs a thing of the past. Oil Ace models with optional sight chamber offer the technician a visual indication of the waste fluid quantity. This technology reduces the threat of costly damages caused by over- or under-torquing or cross-threading drain plugs.

### Large Offset Collection Pan

Wide offset collection bowl prevents splashing.

### Vacuum Gauge

Ensure peak performance with easy-to-read vacuum gauge.

### Sight Glass

Inspect oil quality via large, clear evacuation chamber and verify amount extracted.

### Easy to Drain

Pressurize using shop air for easy oil evacuation.

### Vacuum Probes

Variety of flexible suction attachments and adapters included.

### Large 24 Gallon (90 l) Capacity Receiver

Perfect for small to large shops without an evacuation system.



### Typical Applications

- Automotive dealerships
- Fast lube centers
- Service shops
- Heavy-duty dealerships
- Fleet services facilities

### Typical Fluids Handled

- Used oil

### Technical Specifications

Fluid	Used oil
Tank Capacity	24 gallon (90 l)
Evacuation	Pressurized
Receiver Material	Steel
Length	24 in (61 cm)
Width	16 in (40.6 cm)
Height	39 to 70.8 in (99 to 180 cm)
Funnel Size	23.8 in (60 cm)
Dry Weight	50.7 to 73.2 lbs (23 to 33.2 kg)
Instruction Manual	310864

# A full line of fluid receivers to meet your needs!



Oil King™ – 238866



Oil Ace™ – 119577



Oil Drain – 239301



Oil Drain – 239302



Oil Drain – 225272

## Ordering Information

248632 Coolant King Used Anti-Freeze Receiver

## Pumping Systems

**224873 Wall-mount 716 diaphragm pump system**

*Includes:*

241906 716 Diaphragm pump

240684 Air installation kit

240685 Fluid installation kit

224835 Wall bracket kit

240832 Drum-style adapter kit

**222090 Wall-mount 1040 diaphragm pump system**

*Includes:*

236265 1040 Diaphragm pump

240684 Air installation kit

240685 Fluid installation kit

189233 Wall bracket accessory kit

240832 Drum-style adapter kit

## Technical Specifications

Collection bowl size	22 x 24 in (50 x 56 cm)
Inspection port size	3 in (8 cm) thread
Fluid outlet fitting size	3/4 in port
Operating temperature range	30 to 105°F (-1 to 49°C)
Maximum coolant temperature	220°F (104°C)
Semi-pneumatic wheel	10 in (25 cm)
Urethane casters	3 in (8 cm)
Fluid capacity	25 gal (95 l)
Length	24 in (60 cm)
Width	24 in (60 cm)
Height	
with bowl at lowest adjustment	45 in (1.1 m)
with bowl at highest adjustment	72 in (1.8 m)
Dry weight	54 lbs (25 kg)
Instruction Manual	308667

©2012 Graco Inc. 336225 Rev. C 04/12 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Contact us today!

Call **800-533-9655** to speak with a Graco representative, or visit [www.graco.com](http://www.graco.com) for more information.

